



**FEATURES:**

- LONGER WEAR LIFE
- RESISTS CORROSION
- ACCEPTS MORE ABRASIVE PESTICIDE FORMULATIONS
- POLYPROPYLENE BODY & CERAMIC INSERT
- POPULAR NOZZLE SIZES FIT MOST SPRAYERS
- OPERATES AT HIGHER PRESSURES UP TO 300 PSI (20 bar)
- INCORPORATES ISO COLOR CODING SCHEME

CONEJET TIP No.		TIP COLOR (VISIFLO)	ORIFICE DIA. mm	MESH OF SCREEN	CAPACITY IN L/min (LITERS PER MINUTE) AT PRESSURE bar										SPRAY ANGLE AT bar			
TYPE TXA	TYPE TXB				2	3	4	5	6	7	8	10	15	20	2	3	7	20
TXA800050VK	TXB800050VK	PURPLE	0.86	100	0.16	0.19	0.22	0.25	0.27	0.28	0.30	0.33	0.39	0.45	68°	72°	80°	83°
TXA800067VK	TXB800067VK	OLIVE GREEN	1.04	50	0.22	0.26	0.30	0.33	0.36	0.39	0.41	0.45	0.55	0.62	70°	73°	80°	81°
TXA8001VK	TXB8001VK	ORANGE	1.19	50	0.33	0.39	0.45	0.50	0.54	0.58	0.62	0.68	0.82	0.93	71°	74°	80°	80°
TXA80015VK	TXB80015VK	GREEN	1.45	50	0.49	0.59	0.68	0.75	0.82	0.88	0.94	1.0	1.3	1.5	72°	75°	80°	80°
TXA8002VK	TXB8002VK	YELLOW	1.70	50	0.65	0.79	0.90	1.0	1.1	1.2	1.3	1.4	1.7	2.0	73°	76°	80°	78°
TXA8003VK	TXB8003VK	BLUE	2.00	50	0.97	1.2	1.4	1.5	1.7	1.8	1.9	2.2	2.6	3.0	75°	77°	80°	77°
TXA8004VK	TXB8004VK	RED	2.26	50	1.3	1.6	1.8	2.1	2.3	2.4	2.6	2.9	3.6	4.1	76°	78°	80°	80°

**DESCRIPTION:**

TYPE TXA & TXB - - VK CERAMIC VISIFLO CONEJET TIPS

(METRIC)



**Spraying Systems Co.®**

Spray Nozzles and Accessories  
P.O. Box 7900 - Wheaton, IL 60189-7900

Rev. No. 1

Ref.

Data Sheet No.

38010M

SHEET OF